



US006883452B1

(12) **United States Patent**  
**Gieseke**

(10) **Patent No.:** **US 6,883,452 B1**

(45) **Date of Patent:** **Apr. 26, 2005**

(54) **PLUNGING TOWED ARRAY ANTENNA**

(75) Inventor: **Thomas J. Gieseke**, Newport, RI (US)

(73) Assignee: **The United States of America as represented by the Secretary of the Navy**, Washington, DC (US)

(\*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 19 days.

(21) Appl. No.: **10/679,675**

(22) Filed: **Oct. 6, 2003**

(51) Int. Cl.<sup>7</sup> ..... **B63B 21/66**

(52) U.S. Cl. .... **114/244**

(58) Field of Search ..... 114/244, 336, 338,  
114/326, 328; 343/709

(56) **References Cited**

**U.S. PATENT DOCUMENTS**

3,972,046 A *	7/1976	Lombardi	343/709
4,189,703 A	2/1980	Bennett	
4,387,450 A	6/1983	Zachariadis	
4,473,896 A	9/1984	Loeser et al.	

5,309,412 A 5/1994 Bourgeois  
6,307,810 B1 10/2001 Shany et al.

\* cited by examiner

*Primary Examiner*—Ed Swinehart

(74) *Attorney, Agent, or Firm*—James M. Kasischke;  
Michael P. Stanley; Jean-Paul A. Nasser

(57) **ABSTRACT**

A towed antenna system and method of use includes a communication device disposed on a buoyant body attached to a housing by a tether. The housing includes a spool, a reel-wire guide, and a motor. The buoyant body and the reel housing are deployed from and towed at from a submerged platform. Hydrodynamic forces from towing prevent the buoyant body from rising to the surface while maintaining the housing at an equilibrium depth. To establish communication, the tether is released from the spool and the buoyant body rises to the surface. The tether is released until the communication session is over or until the tether is fully deployed. The reel-wire guide prevents the tether from becoming snagged during release. Once the communication session has been completed, the tether is retracted and the buoyant body re-establishes its equilibrium depth.

**10 Claims, 3 Drawing Sheets**

